eSSL AiFace Jupiter

5-inch face terminal that also takes fingerprint, card and password



Key features

- Visible-light face recognition with anti-spoofing against photo, video and 3D mask attacks
- Four verification methods: face, fingerprint, card and password
- Touchless face verification in 1 second or less
- Supplementary light with adjustable brightness
- Door control: electric lock, door sensor, exit button, alarm output and auxiliary input

Specifications

Display	5-inch touch screen
Face capacity	6,000 (standard); 10,000 (optional)
Fingerprint capacity	6,000
Card capacity	10,000
Transaction capacity	200,000
Operating system	Linux
Processor	900 MHz dual-core
Memory	512 MB RAM / 8 GB flash
Camera	2 MP WDR low-light
Face recognition speed	≤ 1 s
Communication	TCP/IP, RS485, Wiegand input/output, Wi-Fi (optional)
Optional card module	13.56 MHz MIFARE IC card
Access control interface	3rd-party electric lock, door sensor, exit button, alarm output, auxiliary input
Power supply	12 V DC, 3 A
Operating temperature	-10 °C to 45 °C
Operating humidity	10% to 90%
Dimensions (W × H × D)	134.93 × 166.93 × 21.5 mm
Software	eTimeTrackLite

eSSL Security Machine, Gurugram
Supply, installation and AMC for eSSL products

Call / WhatsApp: +91 92204 21199
esslsecuritymachine.com

Specifications are taken from eSSL's published data and can change with model revisions. Please confirm the exact version with us before ordering.

Need a price or a site visit? Call or WhatsApp **+91 92204 21199**. We supply, install and service eSSL products in Gurugram. More details at esslsecuritymachine.com