eSSL AiFace Mars

Slim 5-inch face terminal for touchless attendance and one door



Key features

- Visible-light face recognition with anti-spoofing against photo, video and 3D mask attacks
- Verification by face, card or password
- Face recognition in 1 second or less
- Wiegand input/output and RS485 for connecting to access control systems
- Supports EM ID cards; 13.56 MHz MIFARE IC card module optional

Specifications

Display	5-inch touch screen
Face capacity	3,000
Card capacity	3,000
Transaction capacity	150,000
Operating system	Linux
Processor	900 MHz dual-core
Memory	512 MB RAM / 8 GB ROM
Camera	2 MP WDR low-light
Face recognition speed	≤ 1 s
Communication	TCP/IP, RS485, Wiegand input/output, Wi-Fi (optional), USB (optional)
Card support	125 kHz EM ID card; 13.56 MHz MIFARE IC card (optional)
Access control interface	Electromagnetic lock / electric lock, door sensor, exit button, alarm output
Power supply	12 V DC, 3 A
Operating temperature	-10 °C to 45 °C
Operating humidity	10% to 90%
Dimensions (W × H × D)	91.93 × 202.93 × 21.5 mm
Software	eTimeTrackLite

Specifications are taken from eSSL's published data and can change with model revisions. Please confirm the exact version with us before ordering.

eSSL Security Machine, Gurugram
Supply, installation and AMC for eSSL products

Call / WhatsApp: +91 92204 21199
esslsecuritymachine.com

Need a price or a site visit? Call or WhatsApp **+91 92204 21199**. We supply, install and service eSSL products in Gurugram. More details at esslsecuritymachine.com