eSSL AiFace Vesta+PoE

5-inch face terminal rated from -30 °C to 60 °C, with 6,000 faces



Key features

- Visible-light face recognition with anti-spoofing against photo, video and 3D mask attacks
- Face recognition in 0.5 s or less
- Wide operating range: -30 °C to 60 °C
- Wiegand input/output and RS485 for integration
- Optional MIFARE card module and optional Wi-Fi

Specifications

Display	5-inch touch screen
Face capacity	6,000
Card capacity	10,000
Transaction capacity	200,000
Operating system	Linux
Communication	TCP/IP, RS485, Wiegand input/output, Wi-Fi (optional)
Optional card type	MIFARE
Access control interface	Electromagnetic lock / electric lock, door sensor, exit button
Face recognition speed	≤ 0.5 s per face
Power supply	12 V DC, max 3 A
Operating temperature	-30 °C to 60 °C
Operating humidity	10% to 90%
Dimensions (W × H × D)	103.83 × 212.41 × 50.60 mm
Software	eTimeTrackLite

Specifications are taken from eSSL's published data and can change with model revisions. Please confirm the exact version with us before ordering.

Need a price or a site visit? Call or WhatsApp **+91 92204 21199**. We supply, install and service eSSL products in Gurugram. More details at esslsecuritymachine.com