eSSL®
Security at Fingertips



ET-1219

Tripod Turnstile

Specification

- Size(L*W*H) : 280*260*980mm
- Pass width : 550mm
- Power : 35W
- Material : δ=1.5mm SUS304
- Bar Material : SUS201
- Movement : Tripod turnstile movement with anti-pass back function
- Indicator Light : RGB light
- Power Supply : 24V 50W
- Control Unit : Main board
- Communication Interface : Dry contact & RS485
- Pass rate : 35-50 persons/minute
- Temperature : -20℃~+70℃
- Humidity : ≤90% No condensation
- IP : IP4X
- Environment : Indoor and outdoor (outdoor with canopy)

Features

- Reasonable and reliable design, low noise, smooth operation and long service life.
- LED indicator, valid card showing green, illegal card showing red.
- Card can be set "with memory" or "without memory".
- With automatic reset function, i.e. after having access to the gate, the gate automatically restores to the locked state if not pass within the time set.
- Compatible with IC and ID card.
- Extensible to realize access control, attendance, fees and other functions.

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

www.esslsecurity.com

ISO FC CE ROHS