eSSL®
Security at Fingertips

Heavy Duty Automatic Tripod Turnstile

ETA-1000A



Specification

Passage Width : =550mm
Throughput rate : 35p/m
Power Supply : 100 ~240V
Operational Voltage : 24V
Max Power Consumption : 30 W
Frequency : 50~60hz
Prectection Level : 54
Working Temperature : -25 ~ +70°C
Electro - motor Drive : DC
Dimension Excluding Bar : 480x280x980 mm
Net Weight Including Bar : 44kg

Features:

Controller

- Full-Auto mode
- Pure Mechanical mode
- Single or Bi-directional funtion in mechanical and electrical versions
- Automatic reset of barrier arms after each passage
- Adustable time out delay

Operating Mode

- Single passage in the set direction
- Bi-directional passage
- Free passage in the set direction
- Always free or locked

Secondary Controller :

- Housing : Made in metal sheet and painted, in or stainless steel AISI 304 or AISI 316
- Barrier Arms : Stainless steel
- Lid (Optional) : Stainless steel or artificial stone (black / brown)

Colours & Finishes :

- High quality powder coating plus lacquered finish
- Dark grey color high quality powder coating plus lacquered finish
- Sandpaper powder coating with pearl mica effect

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development
www.esslsecurity.com

ISO FC CE RoHS