eSSL F22 (ID + Wi-Fi)

Slim 19.4 mm fingerprint and card door terminal with built-in Wi-Fi



Key features

- SilkID 500 DPI fingerprint sensor, identification under 0.5 s
- Built-in Wi-Fi, TCP/IP, RS485 and USB host
- Wiegand input and output
- Works with exit readers such as FR1200, KR500, JS500E and KR503E-RS
- Slim 19.4 mm body

Specifications

Display	2.8-inch TFT
Fingerprint capacity	3,000
Card capacity	5,000
Transaction capacity	30,000
Fingerprint sensor	500 DPI SilkID
FAR / FRR	≤ 0.0001% / ≤ 1%
Identification speed	< 0.5 s
Keypad	Yes
Communication	TCP/IP, Wi-Fi (built-in), RS485, USB host
Wiegand	In & out
Push data	Yes
MIFARE	Optional
Access control interface	Electromagnetic lock / electric lock, door sensor
Exit readers supported	FR1200, push button, KR500, JS500E, no-touch, KR503E-RS
Power supply	12 V DC, 1.5 A
Operating temperature	0 °C to 45 °C
Operating humidity	20% to 80%
Dimensions (L × W × H)	158.5 × 78.0 × 19.4 mm

eSSL Security Machine, Gurugram
Supply, installation and AMC for eSSL products

Call / WhatsApp: +91 92204 21199
esslsecuritymachine.com

Software	eTimeTrackLite, eBioServer

Specifications are taken from eSSL's published data and can change with model revisions. Please confirm the exact version with us before ordering.

Need a price or a site visit? Call or WhatsApp **+91 92204 21199**. We supply, install and service eSSL products in Gurugram. More details at esslsecuritymachine.com