eSSL FB-E-2200

Flap barrier with lit acrylic retracting flaps and a 0.2 s release



Key features

- Retracting transparent acrylic flaps with red, green and blue lighting
- Unlocks in 0.2 s from a dry-contact input
- Emergency mode supported
- Indoor or sheltered outdoor installation
- Single and double units available

Specifications

Power requirement	100–240 V AC
Working temperature	-28 °C to 60 °C
Working humidity	5% to 80%
Environment	Indoor / outdoor (if sheltered)
Throughput (by reader type)	RFID up to 35/min; fingerprint up to 25/min; face up to 11/min
Lane width	550 mm
IP rating	IP44
Input	Dry contact
Unlock time	0.2 s
Dimensions (L × W × H)	1200 × 280 × 980 mm
Net weight	52 kg (single unit); 87 kg (double unit)
LED indicator	Yes
Cabinet and lid	SUS304 stainless steel
Barrier	Transparent acrylic, lit (red, green, blue)
Barrier movement	Retracting
Emergency mode	Yes
Security level	Medium
MCBF	3 million cycles

eSSL Security Machine, Gurugram
Supply, installation and AMC for eSSL products

Call / WhatsApp: +91 92204 21199
esslsecuritymachine.com

Specifications are taken from eSSL's published data and can change with model revisions. Please confirm the exact version with us before ordering.

Need a price or a site visit? Call or WhatsApp **+91 92204 21199**. We supply, install and service eSSL products in Gurugram. More details at esslsecuritymachine.com