eSSL®
Security at Fingertips

Full Height Turnstile - Single Door

FHT-TL-149



Specification

Power Supply : 100V ~ 240V AC
Control Circuit : 24 V DC
Power Consumption : 30W
Operating Temper renge : -25°C ~ +70°C
Protection level (IP) :≥44 | Humidity : 95%
MCBF : 5 Million Cycles
Hydraulic damper : Adjustable
Solenoid : 24V DC 100%
Throughout : Person
Signal Output : 12V Pulse
Communication Interface : RS485 or TCP IP
Passage width :≤650mm
Frequency :≤50Hz or 60Hz
Electro-magnetic drive : DC
Section version : 90 degree
No of arms : 4 arms
Dimensions : 1630 x 1500 x 2310 mm
Net weight : 220 kg

Feature:

- Designed for secure operation wish aesthetics inland
- Corrosion protected S/S frame
- Minimal exposed hardware
- Heavy Gauge materials ASTM Standard
- Consists of rotor assembly, shield
- Assemnly, barrier section, mechanism housing & ceiling plate
  The barrier can be set to delay closing in 1 ~ 60s after a
- valid card reading
- Single passage in the set direction
  Bi-directional single passage
  Free p[assage in the direction
  Always free or locked

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase.
Actual product may differ slightly to that depicted for ongoing product development
www.esslsecurity.com

ISO FC CE RoHS