eSSL®
Security at Fingertips



FHT-TL-537

Full Height Turnstile

Size (L*W*H)	1400*1300*2230mm
Pass width	600mm
Power	50W
Material	Body δ=1.2mm / fence ϕ=1.0mm SUS304
Movement	molding full-height turnstile movement
Sensor	Limited sensor
Indicator Light	Dynamic indicator light
Drive Unit	Anti-burn solenoid
Power Supply	24V 150W
Control Unit	Main board
Communication Interface	Dry contact & RS485
Pass rate	35-50 persons/minute
Temperature	-20℃~+70℃
Humidity	≤90% No condensation
IP	IP4X
Environment	Indoor and outdoor

Functions & Features

- Reasonable and reliable design, low noise, smooth operation and long service life；
- With function of opening doors automatically under power-off state to meet the need of fire-fighting passage；
- With functions of anti-tail, anti-reverse pass and so on;
- Card can be set "with memory" or "without memory" functions;
- With automatic reset function, i.e. after having access to the gate, the gate automatically restores to the locked state if not pass within the time set;
- With infrared anti-clip function (anti-clip when gate is open or running);
- Compatible with IC, ID card, scanning and face recognition,etc.
- Two modes of operation are available: open or closed.
- Various working modes are available, including two-way card reading and one-way card reading,etc

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

www.esslsecurity.com

ISO FC CE ROHS