eSSL®
Security at Fingertips



HE-02

RFID Encoder and Updater

Technical Specifications :
- Power Supply: DC5V +-10%
- Current Consumption: 75mA
- Reading Distance: 0-50mm
- Card Operation Frequency: 13.56MHZ
- Indicator (LED/Beeper): Power /Communication /Good

Features :
- Compatible card type: Mifare Classic 1K, Mifare Classic 4K, CUP card.
- Card Standard: ISO1443 A&B read/Write.
- Communication: USB, Standalone type.
- Driver: No additional driver needed, Compatible with windows 7, 8, 10, 11.

Physical Characteristics :
- Dimensions: 127(L)*87(W)*39(H) mm
- Color: Black

Operating Conditions :
- Temperature:-20-60C
- Storage:-20-60C

Built –in-Peripherals :
- LED: 2 single –color: Red and Green
- Buzzer: Monotone

USB Host Interface :
- Connector Type: Standard Type A
- Power Source: From USB port
- Supply current: 5V
- Protocol: USB HID Keyboard Class

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.
www.esslsecurity.com

ISO FC CE