eSSL®
Security at Fingertips



HL500

Smart Hotel Door Lock

TECHNICAL SPECIFICATIONS

- Power Supply: 4xAA alkaline battery
- Material: Aluminum alloy
- Metal Finishes: Coffee Gold
- Mortise: EURO profile, 60mm backset
- Emergency Opening Options: Emergency Opening with Mechanical cylinder
- Locking Mechanism: Electro-mechanical locking mechanism
- Door Thickness: Standard 40mm-50mm
- Customized Structure, (Used for 30mm or below 30mm)
- Working Temperature: -20°-60°
- RFID Specification :13.56MHZ Technology
- Compatible with ISO 14443 A standard

Features :

- Fashionable aluminum alloy handle and panel design
- Simple Offline installation
- Fully integrated with the Flock hotel locking Platform
- All Communication between the carrier and the electronic lock are encrypted and secure.
- Optical signaling through LED .Dual color blue/red to indicate access authorization.
- Battery Operated 4xLR6 Size AA.
- 1700 access events can be audited
- Euro profile emergency opening by mechanical override
- High strength stainless steel mortise latches.

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.
www.esslsecurity.com

ISO FC CE ROHS