eSSL®
Security at Fingertips



HL600

Smart Hotel Door Lock

TECHNICAL SPECIFICATIONS

- Power Supply: 4xAA alkaline battery
- Battery Location: Inside the back lock
- Material: 304 Stainless Steel
- Metal Finishes: Satin Chrome Finish
- Mortise: EURO profile, 60mm backset
- Emergency Opening Options: Emergency Opening with Mechanical cylinder
- Locking Mechanism: Electro-mechanical locking mechanism
- Door Thickness: Standard 40mm-50mm
- Customized Structure, (Used for 30mm or below 30mm)
- Working Temperature: -20°-60°
- RFID Specification :13.56MHZ Technology
- Compatible with ISO 14443 A standard

• Features :

- Simple Offline installation.
- High Security with 302 stainless steel through advanced hardened high resistance anti-drill plates.
- Fully integrated with the Flock hotel locking platform.
- All communications between the carrier and the electronic lock are encrypted and secure.
- Optical signaling through LED. Dual color blue/red to indicate access authorization.
- Battery operated 4XLR6 size AA .
- Euro Profile Emergency opening by mechanical override.
- 1700 access events can be audited.
- High strength stainless steel mortise latches.

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.
www.esslsecurity.com

ISO FC CE ROHS