
eSSL®
Security at Fingertips

Standalone RFID Time Attendance Access Control System



K990



Specification

Storage Capacity
Users : 40,000
Card Storage : 40,000

Transaction Capacity : 8,00,000
Card reader : Yes
CPU : 32 bit Microprocessor

Audio/Visual
Display : 3.5" Color TFT
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker

Communication
TCP/IP, USB, (Optional : Wifi, GPRS)
Push data : Inbuilt
Standard features : work code,SMS,DLST, Self service query, Status Switch

Power & Environment
Power Supply : DC 12V --- 3Amp
Operating Temperature : 0°C - 45°C
Operating Humidity : 20% - 80%
Dimension (in mm) : (L)210 x (W)157 x (H)40

Major Applications

Time & Attendance, Canteen Management, School Attendance, Production Management, GYm & clubs

Access control
Wiegand : In & Out both 26 or 34 bit (With or without site code)
Relay : 12 V relay for lock EM lock, Bolt Lock or Strike lock
Support Fire Alarm : Yes
Door Sensor : Yes
Anti Passback : Yes
Door Bell : Yes

Exit Readers
Support exit readers : KR500E, JS500E

Optional
Battery : Yes
Card readers : Yes
Communication : WiFi/GPRS
Card Type : Mifare/HID Prox

Compatibility
- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer (Optional)

Compatible Software and SDK
- etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com

ISO FC CE RoHS