eSSL®
Security at Fingertips

Standalone RFID Time Attendance & Access Control System

S-990A



Specification

Card Capacity : 30,000
Transaction Storage : 1,00,000
Card Reader : Yes
Push data : Standard
CPU : 32 bit Microprocessor - 800Mhz
FAR : <=0.0001% / FRR : <=1%
Identication Speed : <=0.1 sec
Algorithm Ver : NA
Display : 2.8” TFT
Keypad : 4 x 4 with 5 function Keys
Schedule Bell/Speaker : Mini Speaker
Communication : RS232/485, TCP/IP
Standard Features : work code,SMS,DLST,
Self service query, Status Switch
Power Supply : 12V DC , 1.5Amp
Operating Temprature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 210 x 157 x 40mm
Access Control : Wiegand : In & Out
both 26 or 34 bit (With or without site code)

Relay : 12 V relay for lock EM lock,
Bolt Lock or Strike lock
Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : KR500E / Exit Button, 101HE
Battery : Yes / Card Readers : Yes
Communication : GPRS, Wifi (Optional)
Printer : Optional

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com

ISO FC CE RoHS

eSSL Security Machine
ATTENDANCE · ACCESS · SECURITY
eSSL Security Machine, Gurugram
Supply, installation and AMC for eSSL products
Call / WhatsApp: +91 92204 21199
esslsecuritymachine.com