eSSL®
Security at Fingertips

Swing Barrier

SB-TL-129



Specification

Passagewidth:≤550mm
Throughputrate:30P/M
PowerSupply:100V~240VAC
OperationalVoltage:24VDC
MaxPowerConsumption:30W
Frequency:50Hz~60Hz
ProtectionLevel(IP):54
WorkingTemperature:-25°~+70°
Electro-magneticDrive:DC
Dimensionexcludingbars:
800X480X980mm
Newweight(IncludingBars):40kg

Features

-- Use IC cards, ID cards, bar code or magnetic cards as automatic identification system.
-- Display has been in use for statistics and numbers
-- with voice and strobe light alerts
-- A combination of infrared sensors and police anti-illegal entry into pedestrian access.
-- Double anti-clipping function, photocell anti-clipping and mechanical anti-clipping
-- The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
-- Single passage in the set direction
-- Bi-directional single passage
-- Plastic toughened glass
-- Always free or locked

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development
www.esslsecurity.com

ISO FC CE RoHS