eSSL®
Security at Fingertips



Multi-Biometric Time Attendance & Access Control System

SFace900

Specification

Face Capacity : 3,000
Fingerprint Capacity : 4,000
Card Capacity : 10,000
Logs Capacity : 100,000
Display : 4.3-Inch Touch Screen
Communication : TCP/IP, USB Host,
Standard Functions : Automatic
Status Switch, Self-Service Query,
Work Code, SMS DST, T9 Input,
9 Digit User ID, Scheduled Bell, Photo ID
Interface for : 3rd Party Electric Lock,
Door Sensor, Exit Button, Alarm
Wiegand Signal Output
Optional Functions : ID/MiFareCard, Wi-Fi,
3G, ADMS, 2000 mAH Backup Battery
Power Supply : 12V 3A
Operating Temperature : 0 °C- 45 °C
Operating Humidity : 20%-80%
Dimensions :195.5*166.5*120mm
(Length*Width*Thickness)
Package Weight : 1.6 kg

Features

- 3,000 face and 4,000 f
- Multi-languages
- High verification Speed
- Optional battery backup
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification
- Outside installation (maximun 12,000 lux)

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com

ISO FC CE RoHS