eSSL®
Security at Fingertips

Multi-Biometric Time Attendance & Access Control System



SilkBio-101TC



Specification

Storage Capacity
Face Capacity : 2,000
Fingerprint Capacity : 3,000
ID Card Capacity : 3,000
Transaction Capacity : 1,00,000

Communication
TCP/IP, USB-Host, Wi-Fi(Optional)
Push Data : Yes

Standard Functions
Work Code, SMS, DST, Scheduled-bell, Self-Service Query, Automatic Status Switch Photo ID, T9 Input, Camera, 9 digit user ID, Built-in Battery, Multiple Verify Mode, External Bell
Access Control Interface : Lock, Door Sensor, Exit Button, Alarm

Optional
Optional Functions : Mifare

Visual
Display : 2.8-inch TFT Screen

Power & Environment
Operating Temperature : 0°C ~ 45°C
Power Supply : DC 12V --- 1.5A
Operating Humidity : 20% - 80%
Dimensions (in mm) : (L)180 x (W)154 x (H)34.2

Features
- Multi-biometric fast verification
- Touch Keypad
- Infrared auto-turning on function to save power
- Quick recognition of dry, wet and rough fingers
- Multi-language supported
- Built-in 2000mAh backup battery to extend operation time
- Prevents duplicated face registration and supports fake face detection function

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com

ISO FC CE RoHS