eSSL®
Security at Fingertips



Vega+W+POE

Technical Specifications:

Display	2.4"@ TFT Color LCD Screen (240 * 320)
Operation System	Linux
Hardware	CPU: Dual Core@1.0GHz RAM: 128MB; ROM: 256MB Speaker: 8ohm±15% @1.0W Physical Keypad: 17 Keys
Authentication Method	Fingerprint / Card / Password (Physical Keypad)
Fingerprint Template Capacity	3,000 (1: N)
Card Capacity	3,000 (1: N)
User Capacity	3,000 (1: N)
Transaction Capacity	200,000
User Password Length	6 - 8 digits
Fingerprint Authentication Speed	less than 0.5 sec
False Acceptance Rate (FAR) %	FAR ≤ 0.0001%
False Rejection Rate (FRR) %	FRR ≤ 0.01%
Card Type	Proximity Card @ 125 kHz (Standard) Mifare Card @ 13.56 MHz (Optional)
Communication	TCP/IP; Wi-Fi ; Wiegand (Input or Output); RS485; USB
Access Control Interface	Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button, Alarm Output
Power Supply	DC 12V 1.5A PoE: IEEE 802.3
Operating Temperature	-10°C to 55°C
Operating Humidity	10% to 90% RH (Non-condensing)
Dimensions	205.7mm * 82.7mm * 33mm (L * W * H)
Ingress Protection Rating	IP65

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.
www.esslsecurity.com

ISO FC CE ROHS